

Gel can flow! Now
also from hobbocks.

FAIR INNOVATION ACHEMA 2018

New - Gel-pump for hobbock,
diameter 340 mm

www.gruen-pumpen.de

FIRST KEY DATA

viskosity	grease or gels with follow plate
material pump	stainless steel
tube length	500 mm for Hobbock 30 I, height 403 mm
tube diameter	40 mm
discharge pressure	1 1/4" AG
weight	3,5 kg
temperature limit	80 °C
material seal	carbon, ceramic, viton
rotor	stainless steel 1.4571
stator	PTFE



DATA SHEET ACHEMA 2018

positive displacement pump SB40-ds 20.1 PTFE



0,37 kW 230V, switch

0,55 kW 400V, 900/min



pump data		SB40-ds 20.1
capacity (max)	kg/min	see motor data
pressure (max)	bar	see motor data
viscosity		grease or gels with follow plate
material pump		stainless steel
tube length	500 mm	for Hobbock 30 l, height 403 mm
tube diameter	mm	40
discharge pressure	OT	1 1/4"
weight	kg	3,5
temperature limit	°C	80
material seal		carbon, ceramic, viton
rotor		stainless steel 1.4571
stator		PTFE

SB40-ds 20.1-PTFE-500	ord.-no.	652-0030			
motor data	Weight	pressure	capacity	pressure	capacity
speed 1400/min	kg	bar	kg/min	bar	kg/min
		water		in application	
0,75 kW, 230V, switch, cable	11	5	23	depending on viscosity	
0,37 kW, 230V, switch, cable	7	1	23		
0,37 kW, 400V, terminal box	7	2	23		
0,55 kW 400V, 900/min terminal box	13	5	15		

accessories		ord.-no.	
protection switch 400 V		810-0023	
frequency inverter			
follow plate	D=340 mm	840-0250	
hose connection IG 1 1/4"-DN25	DN25	825-0002	safe connection for hose with pump
hose PVC	2m DN25	825-0002	
reduction AG 1 1/4"-IG 1/2"		825-0172 825-0225	adaption to anchor hole
trolley			fastening of the pump, easy moving

grün-pumpen gmbh
 Otto-Schott Str. 19
 D-97877 Wertheim
 Telefon +49 93 42 9 35 16-0
 Telefax +49 93 42 9 35 16-29
 info@gruen-pumpen.de
 www.gruen-pumpen.de

g
 grün-pumpen
 take out, what's in.